

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH)

OneShot Road Diesel Pro

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

	Product name:	OneShot Road Diesel Pro		
	Product code:	OS1964RP		
	Product description:	Liquid fuel additive for diesel or gas oil.		
	CAS No.: EC No.: Index No.:	Not applicable. Not applicable. Not applicable.		
1.2	Relevant identified uses of the substance or mixture and uses advised against			
	Identified use(s):	Liquid fuel additive for diesel or gas oil.		
	Uses advised against:	Follow supplier's recommendations on correct use of the product.		
1.3	Details of the supplier of the safety data sheet			
	Manufacturer/Supplier:	Sirius Marine Services Ltd. Redstone Wharf Sandy Lane Industrial Estate Stourport on Severn Worcestershire DY13 9QB United Kingdom		
	Telephone:	01299 871 048		
	E-mail:	info@siriusmarine.co.uk		
	Website:	www.siriusmarine.co.uk		
1.4	Emergency telephone number			
	In case of emergency, call:	07990 848 868 (24 hours, 7 days)		



www.siriusmarine.co.uk

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No. 1272/2008 (CLP)

Acute Tox. 4; H302 Asp. Tox 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 Aquatic Chronic 2; H411 EUH066

2.1.2. Classification according to Directive 67/548/EEC & Directive 1999/45/EC

Harmful; Xn; R20/21/22 Irritant; Xi; R38 Harmful; Xn; R65 R66 Dangerous for the environment; N; R51/53

2.2 Label elements

2.2.1. Label according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



Signal Word:

Danger.

Hazard Statement(s):	 H302: Harmful if swallowed. H304: May be fatal if swallowed and enters airways. H312: Harmful in contact with skin. H315: Causes skin irritation. H319: Causes serious eye irritation. H222: Harmful if inhalod.
	H332: Harmful if inhaled. H411: Toxic to aquatic life with long lasting effects.



Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH)

Precautionary Statement(s):	 P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves / protective clothing / eye protection / face protection. P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331: Do NOT induce vomiting. P405: Store locked up. P501: Dispose of contents/container to: disposal should be in accordance with local, state or national legislation.
Supplemental Hazard information (EU):	EUH066: Repeated exposure may cause skin dryness or cracking.

2.2.2. Label according to Directive 67/548/EEC or Directive 1999/45/EC

Hazard symbol(s):



Indication(s) of danger:	Harmful; Dangerous for the Environment.
Risk phrase(s):	 R20/21/22: Harmful by inhalation, in contact with skin and if swallowed. R38: Irritating to skin. R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety Phrase(s):	 S23: Do not breathe fumes/vapour. S24/25: Avoid contact with skin and eyes. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S29: Do not empty into drains. S35: This material and its container must be disposed of in a safe way. S36: Wear suitable protective clothing. S39: Wear eye/face protection.



Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH)

S51: Use only in well-ventilated areas.S61: Avoid release to the environment. Refer to special instructions/Safety Data Sheets.S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3 Other hazards

None known.

SECTION 3: Composition

3.2 Mixtures

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
2-Ethylhexyl nitrate	30-50	27247-96-7	248-363-6	-	Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Aquatic Chronic 2; H411 EUH044 EUH066
Distillates (petroleum), hydrotreated light	5-15	64742-47-8	265-149-8	649-422-00-2	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411
2-Ethylhexan-1-ol	2-10	104-76-7	203-234-3	-	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335
Butanedioic acid, polyisobutenyl	2-10	68610-89-9	-	-	Eye Irrit. 2; H319
Solvent naphtha (petroleum), heavy arom.	< 1	64742-94-5	265-198-5	649-424-00-3	Asp. Tox. 1; H304 Skin Irrit 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411



www.siriusmarine.co.uk

Classification according to Directive 67/548/EEC

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
2-Ethylhexyl nitrate	30-50	27247-96-7	248-363-6	-	Xn; R20/21/22 R44 R66 N; R51/53
Distillates (petroleum), hydrotreated light	5-15	64742-47-8	265-149-8	649-422-00-2	R10 Xi; R38 Xn; R65 R67 N; R51/53
2-Ethylhexan-1-ol	2-10	104-76-7	203-234-3	-	Xn; R20 Xi; R36/37/38
Butanedioic acid, polyisobutenyl	2-10	68610-89-9	-	-	Xi; R36
Solvent naphtha (petroleum), heavy arom.	< 1	64742-94-5	265-198-5	649-424-00-3	Xi; R36/38 Xn; R65 N; R51/53

See Section 16 for full description of R phrases and H statements.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

INHALATION:	Obtain medical attention immediately. Remove patient form exposure, keep warm and at rest.
SKIN CONTACT:	Remove contaminated clothing immediately. Rinse affected area with copious amounts of water. Then wash area with soap and water for at least 15 minutes. If symptoms persist, obtain medical attention. Discard of or wash thoroughly contaminated clothing.
EYE CONTACT:	Obtain medical attention immediately. Remove contact lenses if present and easy to do. Wash eyes immediately with plenty of water for at least 15 minutes.
INGESTION:	Obtain medical attention immediately Provided the patient is conscious wash mouth out with water and provide patient with 200-300 ml of water to drink. Do not induce vomiting.



www.siriusmarine.co.uk

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact causes redness and pain. Repeated exposure may cause skin dryness or cracking. Eye contact causes watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into lungs may result in chemical pneumonia.

4.3 Indication of any immediate medical attention and special treatments needed:

In case of accident or if you feel unwell, seek medical advice immediately. If in contact with eyes, wash eyes immediately and seek immediate medical attention. If swallowed, patient should be monitored for signs of breathing difficulty as effects of aspiration may be delayed for up to 48 hours. If breathing is laboured, oxygen should be administered by qualified personnel.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media

Suitable extinguishing media:	Foam, CO2 or dry powder. For large fires, use water.
Unsuitable extinguishing media:	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Combustible liquid and vapour. Vapour may form explosive mixture with air.

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, various hydrocarbons and nitrogen oxides.

5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

Flash point: 67-80°C (closed cup).

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Avoid inhalation of fumes/vapours. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate. (See Section 8).



www.siriusmarine.co.uk

6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (See Section 8). Contaminated clothing should be thoroughly cleaned.

6.2 Environmental precautions

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and materials for containment and clearing up

6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

6.3.2 For cleaning up

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated absorbent material into a container for disposal. The containers used should be plastic-lined sealable drums. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

6.3.3 Other advice

None.

6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Use only outdoors or in a well-ventilated area. Provide adequate ventilation, including local extraction, to minimise exposure. Avoid breathing fumes/vapours. Avoid contact with skin and eyes. Wear suitable personal protective equipment (See Section 8).

Do not eat, drink or smoke in the vicinity of the product. Wash exposed skin after use. Contaminated work clothing should not be allowed out of the workplace. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.



www.siriusmarine.co.uk

7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep from direct sunlight. Store locked up. Store only in the original container. Store in a cool, well ventilated place. Maximum handling temperature: 50°C. Empty containers retain product residue and can be hazardous.

Keep away from oxidising agents.

7.3 Specific end uses(s)

Liquid fuel additive for diesel or gas oil.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

No occupational exposure limits assigned.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation, including local extraction, to minimise exposure.

8.2.2 Personal protection

Eye protection:	Goggles giving complete protection to eyes. (EN 166)	
Skin protection:		
Hand protection:	Chemical resistant gloves. (EN 374).	
Other:	Long sleeve protective clothing. Plastic apron. Rubber boots.	
Respiratory protection:	In the case of insufficient ventilation, wear suitable respiratory equipment. (BS EN 14387:2004+A1)	
Thermal hazards:	Wear suitable temperature resistant gloves and protective clothing if the product is heated.	

8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.



www.siriusmarine.co.uk

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Amber to red liquid.
Odour:	Hydrocarbon.
Odour threshold:	Not available.
pH:	Not available.
Melting/freezing point::	Not available.
Initial boiling point and boiling range:	Not available.
Flash point:	67-80°C (closed cup).
Evaporation rate:	Not available.
Flammability (solid; gas):	Not applicable.
Upper/lower flammability or explosive limits:	Not available.
Vapour pressure:	Not available.
Vapour density:	Not available.
Relative density:	0.89 - 1 (Water = 1)
Solubility(ies):	Immiscible in water. Miscible in aromatic solvents.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition temperature:	425°C
Decomposition temperature:	Not available.
Viscosity:	< 10 cSt (40°C) (Kinematic)
Explosive properties:	Not explosive. Vapour may form explosive mixture with air.
Oxidising properties:	Not oxidising.

9.2 Other information

None.

SECTION 10: Stability and Reactivity

10.1	Reactivity	Reacts with oxidising agents.
10.2	Chemical stability	Stable under normal conditions.
10.3	Possibility of hazardous reactions	No hazardous reactions expected during normal use.



www.siriusmarine.co.uk

10.4	Conditions to avoid	Keep away from sources of ignition, hot surfaces, direct sunlight. Contact with incompatible materials.
10.5	Incompatible materials	Oxidising agents.
10.6	Hazardous decomposition products	Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, various hydrocarbons and nitrogen oxides.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity	Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.
	No data available on the mixture.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Skin sensitisation	No evidence of skin sensitisation.
Respiratory sensitisation	No evidence of respiratory sensitisation.
Germ cell mutagenicity	No evidence of mutagenicity.
Carcinogenicity	No evidence of carcinogenicity.
Reproductive toxicity	No evidence of reproductive toxicity.
Specific Target Organ Toxicity – single exposure	Inhalation of high concentrations of vapour may cause irritation to the respiratory tract.
Specific Target Organ Toxicity – repeated exposure	Based on the available data, the classification criteria are not met.
Aspiration hazard	May be fatal if swallowed and enters airways. Risk of aspiration into lungs resulting in chemical pneumonia.
Information on likely routes of exposure	
Inhalation Skin contact	Harmful if inhaled. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Harmful in contact with skin. Causes skin irritation.



Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH)

Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed. Ingestion may cause irritation to mouth, throat and digestive tract. May be fatal if swallowed and enters airways. Risk of aspiration into lungs resulting in chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Skin contact causes redness and pain. Repeated exposure may cause skin dryness or cracking. Eye contact causes watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into lungs may result in chemical pneumonia.
Mixture versus substance information	No data available.

None.

SECTION 12: Ecological Information

Other information

12.1	Toxicity	Toxic to aquatic life with long lasting effects.	
		M factor: 1	
12.2	Persistence and degradability	No data available.	
12.3	Bioaccumulative potential	No data available.	
12.4	Mobility in soil	No data available.	
12.5	Results of PBT and vPvB Assessment	The product does not contain substances assessed to be PBT or vPvB.	
12.6	Other adverse effects	None known.	

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

To be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.



Safety Data Sheet According to Regulation (EC) No.

1907/2006 (REACH)

www.siriusmarine.co.uk

SECTION 14: Transport Information

ADR

14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of
14.0		the product.
ADN		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
RID		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
ΙΑΤΑ	/ICAO	
14.1	UN Number	3082
14.2	UN Proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes



Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH)

14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
IMDG	i	
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant.
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	The product is not intended to be transported in bulk.

SECTION 15: Regulatory Information

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP), Directive 67/548/EEC & Directive 1999/45/EC.
15.2	Chemical Safety Assessment	Not applicable.

SECTION 16: Other Information

Full text of relevant R-phrases and/or H-statements:

Hazard Statement(s):	H226: Flammable liquid and vapour.
	H302: Harmful if swallowed.
	H304: May be fatal if swallowed and enters airways.
	H312: Harmful in contact with skin.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H332: Harmful if inhaled.
	H335: May cause respiratory irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.



www.siriusmarine.co.uk

EUH066: Repeated exposure may cause skin drynes or cracking.	-
Risk phrase(s):R10: Flammable. R20: Harmful by inhalation. R20/21/22: Harmful by inhalation, in contact with skin and if swallowed. 	

Abbreviations:

CAS: Chemical Abstracts Service;

- EINECS: European Inventory of Existing Commercial Chemical Substances
- PBT: Persistent, Bioaccumulative and Toxic.
- vPvB: Very Persistent and Very Bioaccumulative.

References:

Supplier's Safety Data Sheets for ingredients Product formulation Approved Classification and Labelling Guide (Sixth edition) The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 Regulation (EC) No. 1272/2008 of the European Parliament and of the council. EH40/2005, 2nd Ed., 2011.

Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.



Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH)

www.siriusmarine.co.uk

Version history:

Version:	2.0
Issue date:	05/02/2013
Previous Version:	1.0
Issue date of previous version:	08/11/2011
Sections changed from previous version:	1-16